

Castrol Transmax CVT

CVT Fluid

Description

Castrol Transmax CVT, formulated with Smooth Drive Technology™, is a full synthetic fluid for use in continuously variable transmissions (CVT) of most Japanese passenger cars. Its superior technology enables longer transmission life. It can be recommended for use in most passenger cars fitted with push belt or chain technologies. Castrol Transmax CVT, formulated with Smooth Drive Technology™, provides higher torque capacity and enhanced wear protection, extending the fluid performance and giving drivers a smoother drive for longer.

Advantages

- Higher torque capacity
- Enhanced wear protection in the push belt–pulley interface
- Superior operational efficiency with reduced risk of belt-slippage
- Improved oxidative stability with excellent viscosity control

Typical Characteristics

Name	Method	Units	Transmax CVT
Density @ 15C, Relative	ASTM D4052	g/ml	0.849
Colour	Visual	-	red
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	34
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.1
Viscosity Index	ASTM D2270	None	179
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	9200
Pour Point	ASTM D97	°C	-51
Flash Point, COC	ASTM D92	°C	214

Product Performance Claims

Suitable for use where:

Toyota CVT Fluid TC

Toyota CVT Fluid FE

Nissan CVT Fluid NS-1

Nissan CVT Fluid NS-2

Nissan CVT Fluid NS-3

MMC DIAQUEEN ATF SP-III

MMC DIAQUEEN CVT Fluid J1

MMC DIAQUEEN CVT Fluid J4

MMC DIAQUEEN CVT Fluid J4+

Mazda CVTF 3320

Subaru i-CVT Fluid

Subaru i-CVT FG

Subaru Lineartronic High Torque Chain CVTF

Daihatsu AMMIX CVT Fluid DC

Daihatsu AMMIX CVT Fluid DFE

Suzuki CVT Fluid 3320

Suzuki CVT Fluid Green 1

Suzuki CVT Fluid Green 2

Suzuki CVTF TC

Suzuki NS-2

Honda HCF-2 *

Hyundai/Kia SP-III

Chrysler NS-2

Chrysler CVTF+4

Mini Cooper EZL799

Ford CVT23

MB 236.20

* Transmax CVT is suitable for use in all of Honda CVTs except 2001-2007 Model Honda Fit/Jazz which are equipped with Starting Clutch

Castrol Transmax CVT

18 Jul 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com