



Gulf Racing Oil 15W-50 –100% Synthetic PAO + Ester Motor Oil

Gulf Racing SPEC Oils Series Description

Ultra-high-performance engine oils which Gulf proud of in the world. 100% chemically synthetic oils (PAO + Ester) with the forefront and original additive technologies brought strong oil films and lowest friction performances.

Product Description

- The oil is 100% chemical synthetic engine oil using PAO + Ester as base oil.
- The Gulf Racing Oil 15W-50 is an ultra-high-performance engine oil, developed for full-fledged sports cars.
- High temperature and high shear viscosity (HTHS Viscosity) number is high, maintaining strong oil film strength even at high temperature and exhibits excellent metal protection performance.
- Maintaining proper hydraulic pressure even at high temperature and high pressure, ensures engine protection of motorsports vehicles and tuning vehicles with a strong oil film.
- It supports a wide range from motor sports to tuning vehicles, and fully brings out performance.

Features & Benefits

- The Gulf Racing Oil 15W-50 retains a strong oil film and protects the inside of engines, as well as the excellent pick-up, especially in high-rotation range of low-pressure turbo vehicles.
- At high temperatures, SAE 50 thick and strong oil film is formed, and the oil film is always stable at high temperature of 150°C.
- Excellent long-term oil film formation reduces the friction inside engines, prevents parts from wear and delivers full engine performance.
- Excellent oxidation stability reduces the generation of sludge and carbon deposited inside engines and maintains an appropriate engine inside environment.
- From motorsports to tuning vehicles exposed to severe driving conditions, you can use them with confidence.

Specifications, Approvals & Typical Properties



Specifications		15W-50
No formal specifications can be claimed, this Oil contain Performance additives designed to achieve API SN		
Typical Properties	JIS Method	Typical Values
Density @15°C	K 2249-1	0.882
Viscosity @40°C	K 2283	126.70
Viscosity @100°C	K 2283	19.97
Viscosity Index	K 2283	181
Flash Point, °C	K 2265-4	236
Pour Point, °C	K 2269	-35.0
Package		Per Box(Packing)
1 Liter CAN		CAN 1L x 6
20 Liter CAN		CAN 20L

18092019

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. GOTCO-Japan reserves the right to modify and change its products and specifications without prior notice.