



Quality is in our nature

Passenger car engine oils - Fully Synthetic

Eurol Super Lite 5W-30

Fully synthetic oil for gasoline and diesel engines, with or without turbo

Description

Eurol Super Lite 5W-30 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo charged engines and for direct fuel injection systems.

Eurol Super Lite 5W-30 provides an extremely quick and stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Eurol Super Lite 5W-30 not only offers extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Super Lite 5W-30 offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

Eurol Super Lite 5W-30 is also recommended for the BMW engines requiring the BMW Longlife-01<2019 performance.

Specifications

Approved

API SL

Recommended for use

API SN/CF

ACEA A3/B4

VW 502.00

MB 229.3

Renault RN0710

Renault RN0700

VW 505.00

Propriétés physiques

Couleur	brun	
Masse volumique à 20°C	0.848 kg/l	ASTM D 1298
Viscosité, cinématique à 40°C	66.2 cSt	ASTM D 445
Viscosité, cinématique à 100°C	11.2 cSt	ASTM D 445
Indice de viscosité	169	ASTM D 2270
Viscosité, dynamique (CCS)	4529 cP	ASTM D 2602
Base number	10.4 mg KOH/g	ASTM D 2896
Teneur en cendres sulfatées	1.31 wt%	ASTM D 874
Point d'éclair	213 °C	ASTM D 93
Point d'écoulement	-45 °C	ASTM D 97

E100091 Version 3.0, 21-07-2021