



APPLICATIONS

Eni Arum HT 220 is a high quality lubricant, formulated with special synthetic ester that do not leave deposits at high temperature.

It is also reinforced with specific additives that ensure anti-wear properties and outstanding resistance to oxidation.

Expressly recommended for the lubrication of chains, bearings and gears operating at high temperatures (peack up to 200°C).

The high viscosity index reduces viscosity variations at the variations of temperature, always ensuring an effective lubricant film.

Eni Arum HT 220 can be applied with automatic sprayers or with dropper oilers; It can also be applied by hand with a brush.

CUSTOMER ADVANTAGES

- Effective anti-rust protection of all part of the chain and of the lubricated components
- Excellent anti-wear properties that prolong the life of the lubricated components operating even at high temperature
- Good oxidation resistance

SPECIFICATIONS - APPROVALS

- ISO 12925-1 CKS
- DIN 51502 CLP-E





CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	APM 27	-	clear
Density at 15°C	ASTM D 4052	kg/m ³	975
Viscosity at 40°C	ASTM D 445	mm ² /s	220
Viscosity Index	ASTM D 2270	-	140
Flash point (COC)	ASTM D 92	°C	250
Pour point	ASTM D 97	°C	-45

WARNINGS

- **Eni Arum HT 220** is not miscible with polyglycol base oils such as Eni Blasia S and similar products.

