

V O L V O

VOLVO AUTOMATIC TRANSMISSION FLUID 97341 AT101



Volvo Automatic Transmission Fluid 97341 AT101 AT101 is a high performance automatic transmission fluid meeting Volvo standard 1273,41.

Description

Volvo Automatic Transmission Fluid 97341 AT101 is a high performance automatic transmission fluid exceeding the latest industry specifications. It is suitable for use where a Dexron III fluid is demanded.

Application

Volvo Automatic Transmission Fluid 97341 AT101 is developed and recommended for the majority of commercial automatic transmissions. It is also suitable for use in power steering systems, hydraulic applications and some manual transmissions where an automatic transmission fluid is specified.

Why choose Volvo Automatic Transmission Fluid 97341 AT101?

- Fuel economy benefits as the result of selected base oils and additive technology, therefore ensuring lower operating costs.
- Correct friction properties to give smooth transmission operation over a wide range of operational bands.
- Protection against degradation at high operating temperature and extended service.
- Low temperature pumpability and circulation, ensuring cold start performance.
- Compatibility with all conventional seal materials found in transmission units.
- Improved anti-wear protection that contributes to extended transmission life.

VOLVO AUTOMATIC TRANSMISSION FLUID 97341 AT101

Quality specification

- Volvo 97341, AT101
- Approved against Volvo standard 1273,41
- Suitable for use where Dexron IIIG or IIHH fluids are demanded
- Meets Allison C-4

Part number

Contact your local dealer

VOLVO LUBRICANTS

Performance, Protection and Uptime

The use of genuine Volvo Lubricants means the machine will perform at its best for longer, increasing uptime and saving on overall costs. It also means the machine will function as originally intended - with the same fuel saving and performance capabilities, reducing emissions for best possible environmental care.

Volvo Lubricants are a design component of a machine, just like gears or hydraulic system. In the design, effort is put on maximizing shear stability to reach maximum performance over the entire service interval. Volvo Lubricants are tested and approved and meet the highest demands there are in the industry.

GENUINE VOLVO PARTS

Our attention to detail is what makes us stand out. This proven concept acts as a solid investment in your machine's future.

Parts are extensively tested and approved because every part is vital for uptime and performance. Only by using Genuine Volvo Parts can you be sure that your machine retains the renowned Volvo quality.

Typical Properties

Density at 15°C		kg/l	0.855	ASTM D1298
Viscosity at 40°C		cSt	35.8	ASTM D445
Viscosity at 100°C		cSt	7.2	ASTM D445
Viscosity Index			168	ASTM D2270
Pour Point		°C	-51	ASTM D97
Flash Point	min	°C	195	ASTM D92
Colour			red	ASTM D1500

Note: the figures given in the table above are indicative values only.