

**PETRONAS**

TECHNICAL CHARACTERISTICS

SELENIA K**PRODUCT CODE: 1142**

APPLICATION

Synthetic lubricant ideal for the most modern petrol engines. Owing to its unique formula, it warrants high resistance to oxidation, the utmost protection in "Stop & Go" driving and outstanding performance whatever the weather.

SPECIFICATIONS

SAE 5W-40, ACEA A3/B4, API SM,
FIAT 9.55535-M2 CONTRACTUAL TECHNICAL REFERENCE N°F214.I05, GM-LL-B-025 Performance,
VW 502 00/505 00 Performance, RENAULT RN700/RN710 Performance, PORSCHE A40 Performance,
BMW LL-01 Performance, MB 229.3 Performance

TEST DESCRIPTION

| TEST DESCRIPTION | METHOD | UNIT | TYPICAL VALUE |
|-----------------------|------------|-------------------|---------------|
| APPEARANCE | -- | -- | B. & C. |
| DENSITY AT 15°C | ASTM D4052 | g/cm ³ | 0,856 |
| VISCOSITY AT 100°C | ASTM D445 | cSt | 15,0 |
| VISCOSITY INDEX | ASTM D2270 | -- | 175 |
| FLASH POINT Cl. O. C. | ASTM D92 | °C | >200 |
| T.B.N. | ASTM D2896 | mg KOH/g | 10,2 |
| POUR POINT | ASTM D97 | °C | <-33 |
| FOAM AT 24°C | ASTM D892 | cc/s | TRACES/0 |

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT**03/2017**