



PRODUCT DATA SHEET



SUPER CLEAN CHAIN LUBE

Super Clean Chain Lube is the latest innovation in chain lubricant technology, combining unsurpassed anti-wear protection for long chain and sprocket life with an outer protective coating that will not attract dirt, sand or grit. **Super Clean Chain Lube** ABSOLUTELY WILL NOT FLING OFF when used as directed. Suitable for all 'O' 'X' and 'Z' ring and roller type chains for road, off-road and racing use.

Applications

- ◆ For all motorcycle and ATV drive chains used for road and off-road riding
- ◆ For long lasting protection against rust and corrosion
- ◆ For protection against shock loading and severe wear caused by metal-to-metal contact

Features and Benefits

- | | |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| ◆ Superior anti-wear | Special anti-wear additives provide exceptional protection against metal-to-metal contact for longer chain life. |
| ◆ Corrosion protection | Full chain coverage is achieved easily to form a protective coating that is waterproof and will not wash out. |
| ◆ Fast drying | Sprays on and dries quickly into a protective coating that will not fling off or pick up dirt and sand. |
| ◆ White color | Leaves the chain looking factory fresh. |
| ◆ Easy to use | Aerosol spray applicator allows for pinpoint precision and provides complete coverage of the chain quickly and easily with no mess. |

General Description

Super Clean Chain Lube is a high performance motorcycle chain lubricant for road and off-road applications. Its unique formulation in convenient aerosol containers sprays on a lubricant white in color that will not fling off once dry and will not attract dirt or sand.

Product No. 300955

SUPER CLEAN CHAIN LUBE

Product No. 300955

Product No. 99470

Application Instructions

Shake can for 1 minute. Apply on a warm chain. Spray a moderate amount of **Super Clean Chain Lube** on the sprocket contact side of the chain and rotate wheel to assist penetration. Wait 10 to 15 minutes to allow non-tacky coating to set up.

Caution: *Use in a well-ventilated space.*

Product is flammable and should be used with appropriate caution.

Do not spray on a hot surface or in proximity to flames or open fire.

Do not puncture or incinerate container, even when empty.

Always wear safety glasses when using this product.

Keep container away from heat.

<i>To clean nozzle, invert aerosol can and depress nozzle after use.</i>
